

GEOPHYSICAL SURVEY REPORT

North Bradley, Trowbridge, Wiltshire

Client

Autometry Ltd

Survey Report

SUMO-01492

Date

December 2020



Survey Report 01492: North Bradley, Trowbridge, Wiltshire

Survey dates 03 December 2020

Field co-ordinator Simon Lobel BSc

Field Team Jasmin Folland MA
Liam Brice-Bateman BA

Report Date 15 December 2020

CAD Illustrations Thomas Cockcroft MSc

Report Author Thomas Cockcroft MSc

Project Manager Thomas Cockcroft MSc

Report approved Dr John Gater BSc DSc(Hon) MCIfA FSA

SUMO Geophysics Ltd
Cowburn Farm
Market Street
Thornton
Bradford
BD13 3HW

T: 01274 835016

SUMO Geophysics Ltd
Vineyard House
Upper Hook Road
Upton upon Severn
Worcestershire
WR8 0SA

T: 01684 592266

www.sumoservices.com
geophysics@sumoservices.com

TABLE OF CONTENTS

1	LIST OF FIGURES	1
2	SURVEY TECHNIQUE	1
3	SUMMARY OF RESULTS	2
4	INTRODUCTION	2
5	RESULTS	3
6	DATA APPRAISAL & CONFIDENCE ASSESSMENT	3
7	CONCLUSION	4
8	REFERENCES	4

Appendix A Technical Information: Magnetometer Survey Methods, Processing
and Presentation

Appendix B Technical Information: Magnetic Theory

1. LIST OF FIGURES

Figure 01	NTS	Site Location
Figure 02	1:1500	Magnetometer Survey - Greyscale Plot
Figure 03	1:1500	Magnetometer Survey - Interpretation
Figure 04	1:2000	LiDAR Data Plot
Figure 05	1:1500	Minimally Processed Data - Greyscale Plot

2. SURVEY TECHNIQUE

Detailed magnetic survey (magnetometry) was chosen as the most efficient and effective method of locating the type of archaeological anomalies which might be expected at this site.

Bartington Grad 601-2 Traverse Interval 1.0m Sample Interval 0.25m

3 SUMMARY OF RESULTS

- 3.1 A magnetometer survey of 3.5 ha at North Bradley, Trowbridge has not recorded any magnetic responses that could be interpreted as being of definite archaeological interest. Several linear trends and a cluster of pit-like responses have been assigned to the category of uncertain. These anomalies are likely to be a product of agricultural or natural processes. Ridge and furrow ploughing is visible throughout the dataset plus buried services have also been marked.

4 INTRODUCTION

- 4.1 **SUMO Geophysics Ltd** were commissioned to undertake a geophysical survey of an area outlined for development. This survey forms part of an archaeological investigation being undertaken by **Autometry Ltd**.

4.2 Site details

NGR / Postcode	ST 86093 55317 / BA14 0TW
Location	The site is located 2km north of West Wilts Trading Estate and 1km south of Trowbridge. The survey area is bounded to the west by Little Common Lane, to the south by Westbury Road and to the east by Hitachi Capital Vehicle Solutions.
HER	Wiltshire and Swindon
District	Westbury
Parish	North Bradley Civil Parish
Topography	Flat
Current Land Use	Pasture
Geology (BGS 2020)	Bedrock: Oxford Clay Formation - Mudstone Superficial: none recorded
Soils (CU 2020)	Soilscape 18: Slowly permeable seasonally wet slightly acid but base-rich loamy and clayey soils.
Archaeology (KYP 2020)	A search of Know Your Place has revealed that ridge and furrow ploughing (MWI73531) plus numerous ditch and bank field boundaries (MWI73532) are recorded within the survey area. These features are thought to be medieval and/or post Medieval in date and have been identified in 1940-50's Royal Air Force aerial photography and LiDAR. Similar field boundaries plus ridge and furrow is also recorded in the immediate area around the site.
Survey Methods	Magnetometer survey (fluxgate gradiometer)
Study Area	3.5 ha

4.3 Aims and Objectives

To locate and characterise any anomalies of possible archaeological interest within the study area.

5 RESULTS

5.1 ***Probable / Possible Archaeology***

- 5.1.1 No magnetic responses have been recorded that could be interpreted as being of definite archaeological interest.

5.2 ***Uncertain***

- 5.2.1 Several uncertain linear trends and a couple of discrete pit-like responses have been detected in the dataset. They lack the morphological attributes of anomalies that would normally be interpreted as having an archaeological provenance. These magnetic responses probably reflect variations in the underlying geology or may be due to agricultural processes. Consequently, these anomalies have been assigned to the category of *Uncertain*.

5.3 ***Agricultural – Ridge and Furrow***

- 5.3.1 Wide and broad linear responses have been recorded in the dataset and are typical of past ridge and furrow agricultural regimes; the ploughing is better defined in the east of the dataset.

5.4 ***Service***

- 5.4.1 A line of strong dipolar ferrous linear anomalies is visible in the magnetic data crossing the whole field; it is thought to mark the course of a small service pipe. Two shorter linear anomalies are believed to be electric cables connected to an overhead transformer mounted on a small pylon (see 5.5.1).

5.5 ***Ferrous / Magnetic Disturbance***

- 5.5.1 Ferrous responses close to boundaries are due to adjacent fences and gates. A large ferrous response in the south of the survey area is due to the presence of a small pylon. A second ferrous response in the east of the dataset could be the remanence of a pylon base which has been removed but the feet have been left in situ. An area of magnetic disturbance within the dataset is likely to be due to modern disturbance; possibly linked to agricultural processes. Small scale ferrous anomalies ("iron spikes") are present throughout the data and are characteristic of small pieces of ferrous debris (or brick / tile) in the topsoil; they are commonly assigned a modern origin. Only the most prominent of these are highlighted on the interpretation diagram.

6 DATA APPRAISAL & CONFIDENCE ASSESSMENT

- 6.1 Historic England guidelines (EH 2008) Table 4 states that the typical magnetic response on the local soils / geology is generally poor. The results from this survey indicate the presence of ridge and furrow ploughing; as a consequence, there is no *a priori* reason why archaeological features would not have been detected, if present.

7 CONCLUSION

- 7.1 The magnetometer survey has not detected any magnetic responses that could be interpreted as being of definite archaeological interest. Several weak linear trends and a cluster of pit-like anomalies are visible in the dataset and have been assigned to the category of *Uncertain*. It is probable that these anomalies are due to agricultural or natural processes. Ridge and furrow ploughing is also visible throughout the dataset, plus a service pipe and two electric cables have been plotted.

8 REFERENCES

- BGS 2020 British Geological Survey, Geology of Britain viewer [accessed 15/12/2020] *website*: (<http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps>)
- ClfA 2014 *Standard and Guidance for Archaeological Geophysical Survey*. Amended 2016. ClfA Guidance note. Chartered Institute for Archaeologists, Reading
http://www.archaeologists.net/sites/default/files/ClfAS%26GGeophysics_2.pdf
- CU 2020 The Soils Guide. Available: www.landis.org.uk. Cranfield University, UK. [accessed 15/12/2020] *website*: <http://mapapps2.bgs.ac.uk/ukso/home.html>
- EAC 2016 *EAC Guidelines for the Use of Geophysics in Archaeology*, European Archaeological Council, Guidelines 2.
- EH 2008 *Geophysical Survey in Archaeological Field Evaluation*. English Heritage, Swindon
<https://content.historicengland.org.uk/images-books/publications/geophysical-survey-in-archaeological-field-evaluation/geophysics-guidelines.pdf/>
- KYP 2020 Know Your Place, online viewer [accessed 15/12/2020] *website*: <http://www.kypwest.org.uk/>

Standards & Guidance

This report and all fieldwork have been conducted in accordance with the latest guidance documents issued by Historic England (EH 2008) (then English Heritage), the Chartered Institute for Archaeologists (CIfA 2014) and the European Archaeological Council (EAC 2016).

Grid Positioning

For hand held gradiometers the location of the survey grids has been plotted together with the referencing information. Grids were set out using a Trimble R8 Real Time Kinematic (RTK) VRS Now GNSS GPS system.

An RTK GPS (Real-time Kinematic Global Positioning System) can locate a point on the ground to a far greater accuracy than a standard GPS unit. A standard GPS suffers from errors created by satellite orbit errors, clock errors and atmospheric interference, resulting in an accuracy of 5m-10m. An RTK system uses a single base station receiver and a number of mobile units. The base station re-broadcasts the phase of the carrier it measured, and the mobile units compare their own phase measurements with those they received from the base station. This results in an accuracy of around 0.01m.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Grad 601-2	1m	0.25m

Instrumentation: **Bartington Grad 601-2**

Bartington instruments operate in a gradiometer configuration which comprises fluxgate sensors mounted vertically, set 1.0m apart. The fluxgate gradiometer suppresses any diurnal or regional effects. The instruments are carried, or cart mounted, with the bottom sensor approximately 0.1-0.3m from the ground surface. At each survey station, the difference in the magnetic field between the two fluxgates is measured in nanoTesla (nT). The sensitivity of the instrument can be adjusted; for most archaeological surveys the most sensitive range (0.1nT) is used. Generally, features up to 1m deep may be detected by this method, though strongly magnetic objects may be visible at greater depths. The Bartington instrument can collect two lines of data per traverse with gradiometer units mounted laterally with a separation of 1.0m. The readings are logged consecutively into the data logger which in turn is daily down-loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

Data Processing

Zero Mean	This process sets the background mean of each traverse within each grid to zero.
Traverse	The operation removes striping effects and edge discontinuities over the whole of the data set.
Step Correction (De-stagger)	When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

Display

Greyscale/ Colourscale Plot	This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly, all values below the given range are represented by the minimum intensity shade. Similar plots can be produced in colour, either using a wide range of colours or by selecting two or three colours to represent positive and negative values. The assigned range (plotting levels) can be adjusted to emphasise different anomalies in the data-set.
--------------------------------	---

Presentation of results and interpretation

The presentation of the results includes a 'minimally processed data' and a 'processed data' greyscale plot. Magnetic anomalies are identified, interpreted and plotted onto the 'Interpretation' drawings.

When interpreting the results, several factors are taken into consideration, including the nature of archaeological features being investigated and the local conditions at the site (geology, pedology, topography etc.). Anomalies are categorised by their potential origin. Where responses can be related to other existing evidence, the anomalies will be given specific categories, such as: Abbey Wall or Roman Road. Where the interpretation is based largely on the geophysical data, levels of confidence are implied, for example: Probable, or Possible Archaeology. The former is used for a confident interpretation, based on anomaly definition and/or other corroborative data such as cropmarks. Poor anomaly definition, a lack of clear patterns to the responses and an absence of other supporting data reduces confidence, hence the classification Possible.

Interpretation Categories

In certain circumstances (usually when there is corroborative evidence from desk-based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, *Roman Road, Wall*, etc.) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the results.

<i>Archaeology / Probable Archaeology</i>	This term is used when the form, nature and pattern of the responses are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age.
<i>Possible Archaeology</i>	These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth, plough damage or even aliasing as a result of data collection orientation.
<i>Industrial / Burnt-Fired</i>	Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metal-working areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies.
<i>Former Field Boundary (probable & possible)</i>	Anomalies that correspond to former boundaries indicated on historic mapping, or which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary.
<i>Ridge & Furrow</i>	Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases, the response may be the result of more recent agricultural activity.
<i>Agriculture (ploughing)</i>	Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes.
<i>Land Drain</i>	Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains may lead and empty into larger diameter pipes, which in turn usually lead to local streams and ponds. These are indicative of clay fired land drains.
<i>Natural</i>	These responses form clear patterns in geographical zones where natural variations are known to produce significant magnetic distortions.
<i>Magnetic Disturbance</i>	Broad zones of strong dipolar anomalies, commonly found in places where modern ferrous or fired materials (e.g. brick rubble) are present.
<i>Service</i>	Magnetically strong anomalies, usually forming linear features are indicative of ferrous pipes/cables. Sometimes other materials (e.g. pvc) or the fill of the trench can cause weaker magnetic responses which can be identified from their uniform linearity.
<i>Ferrous</i>	This type of response is associated with ferrous material and may result from small items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses similar to ferrous material.
<i>Uncertain Origin</i>	Anomalies which stand out from the background magnetic variation, yet whose form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of <i>Possible Archaeology / Natural</i> or (in the case of linear responses) <i>Possible Archaeology / Agriculture</i> ; occasionally they are simply of an unusual form.

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

Appendix B - Technical Information: Magnetic Theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.1 nanoTeslas (nT) in an overall field strength of 48,000 (nT), can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.




Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning and complex biological or fermentation processes.

Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns; material such as brick and tile may be magnetised through the same process.

Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.


Magnetic survey is carried out using a fluxgate gradiometer which is a passive instrument consisting of two sensors mounted vertically 1m apart. The instrument is carried about 30cm above the ground surface and the top sensor measures the Earth's magnetic field whilst the lower sensor measures the same field but is also more affected by any localised buried feature. The difference between the two sensors will relate to the strength of a magnetic field created by this feature, if no field is present the difference will be close to zero as the magnetic field measured by both sensors will be the same.

Factors affecting the magnetic survey may include soil type, local geology, previous human activity and disturbance from modern services.




Reproduced from Ordnance Survey's 1:25 000 map of 1998 with the permission of the controller of Her Majesty's Stationery Office. Crown Copyright reserved. Licence No: 100018665


	Site Location
	Survey Areas
	



Title:	Site Location	
Client:	Autometry Ltd	
Project:	01492 - North Bradley, Trowbridge, Wiltshire	
Scale:	NOT TO SCALE	Fig No: 01




Title: Magnetometer Survey - Greyscale Plot	
Client: Autometry Ltd	
Project: 01492 - North Bradley, Trowbridge, Wiltshire	
Scale: 0 metres 75 1:1500 @ A3	Fig No: 02




KEY



	Uncertain Origin (Discrete Anomaly / Trend)
	Agriculture (Ridge and Furrow)
	Magnetic Disturbance
	Service
	Ferrous



Title: Magnetometer Survey - Interpretation	
Client: Autometry Ltd	
Project: 01492 - North Bradley, Trowbridge, Wiltshire	
Scale: 0 75 metres 1:1500 @ A3	Fig No: 03



Title:		LiDAR Data Plot
Client:		Autometry Ltd
Project:		01492 - North Bradley, Trowbridge, Wiltshire
Scale:	metres	Fig No:
0	100	04
1:2000 @ A3		




Title:
Minimally Processed Data - Greyscale Plot

Client:
Autometry Ltd

Project:
01492 - North Bradley, Trowbridge, Wiltshire

Scale:
0 metres 75
1:1500 @ A3

Fig No:
05



- Archaeological
- Geophysical
- Laser Scanning
- Measured Building
- Topographic
- Utility Mapping

SUMO Services Ltd, incorporated under the laws of England and Wales,
Company Registration No.4275993.
Registered Office Unit 8 Hayward Business Centre, New Lane, Havant, Hampshire, PO9 2NL