



Warefence

DATASHEET WF 868

WF 868 is a welded mesh system providing a high level perimeter protection with a unique and distinctive appearance. The system also has an excellent through vision which makes it superb for multiple types of application.
Each panel is made from twin galvanised horizontal rods at 8mm diameter positioned each side of a vertical, 6mm bar. Each rod is welded at every intersection point, offering high impact damage resistance at every section. The panel system offers a discrete barbed topping making it extremely difficult to climb.



However, the barbed edge can be positioned at ground level in situations where a flush top is required in places such as schools.
WF 868 fencing panels are positioned at 2.52m centres and have included factory fitted inserts. Throughout the system, the panels are attached using secure, robust steel fixing brackets and M8 diameter bolts which are tamper resistant. Overall the **WF 868** provides the user with a cost effective solution for all boundary requirements which is secure, high impact resistant and offers pleasant atheistic to all locations.

Typical applications for this system include; Schools, Colleges and Universities. It is common to find that local authorities specify 8/6/8 for use in Parks and around Public amenities.

THE LEADING SECURITY FENCE AND GATE MANUFACTURER

© This drawing is the copyright and may not be reproduced in part or in whole without prior written permission

Notes

Revision	Description	Date	Drawn

Client: Dyson

Project: Hangar 89/90
Security Fence

Drawing: Fence Specification Details

Scale: N/A @ A3 Drawn by: AJH

Date: July 23 Checked by: PWH

Drawing Number: Revision:

2023/182/SPEC