SPLIT

Wall mounted unit

FTXP-M



comfora

BLUEVOLUTION

Practically inaudible

Energy saving during standby mode

3-D air flow

Online controller via app

Multi model application

Discreet wall mounted unit providing high efficiency and comfort

› Practically inaudible: the unit runs so quietly, you will almost forget it is there.
› Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
› Silver allergen removal and air purifying filter: captures allergens such as pollen and dust mites.
› 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
› The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation

FTXP-M + RXP-M



Indoor unit				FTXP	20M	25M	35M	50M	60M	71M
Casing	Colour				White					
Dimensions	Unit	HeightxWidthxDepth		mm	286x770x225			295x990x263		
Sound power level	Cooling			dBA	55		58	59	60	62
Sound pressure level	Cooling	High/Medium/Low/Silent operation		dBA	39/33/25/19	40/33/26/19	43/34/27/20	43/39/34/27	45/41/36/30	46/42/37/32
	Heating	Super high/High/Medium/Low/		dBA	-/39/34/28/21	-/40/34/28/21	-/40/35/29/21	42/38/33/30/-	44/40/35/32/-	45/41/36/33/-
Control systems	Infrared remote control				ARC480A53					
	Wired remote control				BRC944B2 / BRC073A1			-		

Efficiency data				FTXP + RXP	20M + 20M	25M + 25M	35M + 35M	50M + 50M	60M + 60M	71M + 71M
Cooling capacity	Min./Nom./Max.			kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3
Heating capacity	Min./Nom./Max.			kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.7	1.7/7.0/8.0	2.3/8.2/9.0
Power input	Cooling	Min./Nom./Max.		kW	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	0.320/1.385/1.826	0.332/1.824/2.980	0.449/2.689/3.274
	Heating	Min./Nom./Max.		kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	0.440/1.579/2.356	0.456/1.928/2.787	0.617/2.571/3.306
Space cooling	Capacity	Pdesign		kW	2.00	2.50	3.50	5.0	6.0	7.1
	Energy efficiency class				A++					
	SEER				6.79	6.92	6.62	7.30	6.82	6.20
	Annual energy consumption			kWh/a	103	126	186	240	308	401
Space heating (Average climate)	Capacity	Pdesign		kW	2.20	2.40	2.80	4.60	4.80	6.20
	Energy efficiency class				A++			A+		
	SCOPnet/A				4.69	4.65	4.68	4.42	4.12	4.04
	Annual energy consumption			kWh/a	662	728	845	1,463	1,638	2,166
Nominal efficiency	EER				4.02	3.83	3.49	3.61	3.29	2.64
	COP				4.77	4.36	4.02	3.80	3.63	3.19

Outdoor unit				RXP	20M	25M	35M	50M	60M	71M
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275			734x870x373		
Sound power level	Cooling			dBA	60		62	61	63	66
	Heating			dBA	61		62	61	63	65
Sound pressure level	Cooling	High/Nom.		dBA	46/-		48/-	-/47	-/49	-/52
	Heating	High/Nom.		dBA	47/-		48/-	-/49		-/52
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46					
Operation range	Heating	Ambient	Min.~Max.	°CDB	-15~18					
Refrigerant	Type/Charge/GWP			kg/TCO_2eq	R-32/0.55/0.37/675.0		R-32/0.70/0.48/675.0	R-32/0.90/0.61/675	R-32/1.15/0.78/675	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240					

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN19-046 02/19

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.