integral LED

Product Specification Sheet

# OUTDOOR STAINLESS STEEL DOWN WALL LIGHT PIR IP54 1xGU10 BLACK INTEGRAL

ILDED045



Add a designer look to your home exterior with the Integral LED Stainless Steel Outdoor range. Completed with a sleek, stylish light ring and brushed finish, these wall mounted lights have a luxurious, contemporary appeal. The down facing beam gives a wash of light across the mounting surface providing excellent illumination whether for your porch, driveway or garden. IP54 Splashproof and hardwearing, the light utilises a PIR motion sensor to automatically switch on as you walk past, making it an ideal addition to any outdoor area. Choose from our wide range of compatible GU10 lamps for a variety of lighting effects.

## Details

| | |
|---|---|
| **Quick Order Code:** | 573606 |
| **Barcode:** | 5055788285649 |
| **Category:** | Luminaires |
| **Range Name:** | Stainless Steel Wall Light |
| **Product Type:** | Outdoor |
| **Product Body Finish:** | Black |
| **Market Segment:** | Residential Outdoor |
| **Warranty (Years):** | 2 |
| **CE RoHS:** | Yes |

## Physical Data

| | |
|---|---|
| **Product Length (mm):** | 149 |
| **Product Depth (mm):** | 116 |
| **Product Width (mm):** | 68 |
| **Product Weight (g):** | 550 |
| **Optic:** | Polycarbonate diffuser |
| **Material:** | Stainless Steel, PC |
| **Construction:** | Stainless Steel body with PC diffuser |
| **Luminaire Fixing:** | Wall Mounted |
| **Placement / Application:** | Outdoor, General Lighting |

## Electrical Data

| | |
|---|---|
| **Voltage Range (v):** | 220-240 |
| **Input Voltage (V):** | 220-240 |
| **Driver Included:** | No |

| | |
|---|---|
| **Electric Current:** | AC |
| **EN:** | EN 60598, EN 55015, EN 61547, EN 61000 |
| **LVD Certified:** | Yes |

## Light Data

| | |
|---|---|
| **Sensor / Overide:** | Yes |

## Environment

| | |
|---|---|
| **EN:** | EN 60598, EN 55015, EN 61547, EN 61000 |
| **LVD Certified:** | Yes |
| **CE RoHS:** | Yes |
| **EU Luminaire:** | L |
| **Hg 0% (Mercury Free):** | Yes |
| **IK Rating (Impact Protection):** | IK08 |
| **IP Rating (Ingress Protection):** | IP54 |
| **Lowest Operating Temperature (°C):** | -20 |
| **Maximum Operating Temperature (°C):** | 40 |

## Packaging

| | |
|---|---|
| **Package Weight (g):** | 600 |
| **Package Length (mm):** | 155 |
| **Package Width (mm):** | 72 |
| **Package Depth (mm):** | 122 |
| **Qty per euro pallet:** | 800 |



Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE