



KEY

- EXISTING FOUL SEWER
- EXISTING PRIVATE SURFACE WATER CULVERT
- EXISTING HIGHWAYS DRAIN
- PROPOSED PRIVATE FOUL WATER DRAINAGE
- PROPOSED PRIVATE SURFACE WATER DRAINAGE
- 450Ø POLYPROPYLENE INSPECTION CHAMBER
- 320Ø MINI-ACCESS CHAMBER
- 1240x675 RECTANGULAR BRICK CHAMBER
- SURFACE WATER RODDING EYE
- INDICATIVE RWP/SVP
- TANKED 'TYPE C' PERMEABLE BLOCK PAVING WITH FIN DRAIN OUTLET
- PERMEABLE PAVING BAFFLE
- PERMEABLE PAVING DISTRIBUTION TANK
- INDICATIVE SPOT LEVEL
- SILT TRAP

NOTES

DRAINAGE STRATEGY FOR PLANNING PURPOSES ONLY AND SUBJECT TO DETAILED DESIGN IN ACCORDANCE WITH BUILDING REGULATIONS APPROVED DOCUMENT H. SUBJECT TO SETTING OUT OF SVPS, RWPS AND DETAILED LEVELS DESIGN. ALL LEVELS ARE INDICATIVE AND SUBJECT TO DETAILED LEVELS DESIGN.

C	PLANNING ISSUE	07.08.25	RP	PS
B	UPDATED SITE PLAN	19.06.25	RP	PS
A	FIRST ISSUE	06.06.25	RP	PS
REV.	DESCRIPTION	Date	BY	CHK

DESIGN BY:

CLIENT:

DRAWING STATUS: **PLANNING APPLICATION**

SCALE @ A1: 0 1:200 10 metres

PROJECT: **WYNSOME STREET, SOUTHWICK**

TITLE: **DRAINAGE STRATEGY**

PROJECT No:	DRAWING No:	REV:
19862	19862-TUM-PL-XXX-0200	C