


Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

Table 1 – Light Fittings

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
L1	Fire Rated Downlight	HiSPEC Yarra PRO 3 CCT HSFRLED6LP	LED / 6W Dimmable	540lm	3000K	White	Recessed	Ø86 x 30.7H	Fire Rated Dimmable	
L2	Fire Rated Tilt Downlight	HiSPEC Brisbane HSFRTLWH	LED / 5W / GU10 Dimmable	-	3000K	Matte White	Recessed Tilttable	Ø96 x 96H	Fire Rated Dimmable	
L3	Small Downlight	Hacel Nano ID1550JLED3061630	LED / 6W / Switch Dim	979lm	3000K	White	Recessed	Ø54 x 55H	Switch Dim Reflector - Standard Beam 36°	
W1	Wall Mounted Lamp in Brasserie	Felix Henley Wall Light Brass	LED / B22	-	3000K	Brass	Wall Mounted	240W x 180H	Dimmable	
W2	Wall Mounted Lamp in Bedrooms	Henley Fully Adjustable Wall Light WL-029-0009-AB	LED / 5.3W / GU10 Dimmable	-	3000K	Antique Brass	Wall Mounted Adjustable Position	Width: 36cm, 13cm min Depth: 39cm max, 18cm min Height: 36cm max, 13cm min	Dimmable	
W3	Wall Mounted Lights Toilets Ground Floor	Pure White Lines Lazio Horizontal PWL78411	LED / 2 x G9 / Dimmable	-	3000K	Brass	Wall Mounted	80W 130D 400H	Dimmable	

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
W4	Picture Light	Felix Lighting Dalton Wall Light	LED / 3W/ G9 Dimmable 2No. bulbs per fitting	-	3000K	Brass	Wall Mounted	Width - 340mm Projection - 160mm	Dimmable	
W5	Wall Light Corridors	Kiro Patricia Lobo Holloways of Ludlow Large 15879_10023	LED / 40W / G9 Dimmable		3000	Cocoa Brown	Wall Mounted	200H 248W	Dimmable	
W6										
W7	Wall Light Toilet, Hall & Stair	Pure White Lines Amerise	LED / 2 x G9 / Dimmable	-	3000	Clear Glass	Wall Mounted	270W 190D 350H	Dimmable	
W8	Wall Light Bathrooms in Bedrooms	Frtiz Fryer Ledbury Wall Light Bronze Ribbed 13381_75082_75989	LED / E27	-	3000	Bronze Ribbed	Wall Mounted	260H 140W 155D	Dimmable	

MAX FORDHAM

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
W9	Wall Light Bathrooms in showers	Old School Electric Oval Bulkhead Brass Large Holloways of Ludlow 5774_67354	LED / E27 Dimmable	-	3000K	Brass	Wall Mounted	160W 250H 104D	Dimmable	
B1	Bar Lamp in Bar Area	Felix Lighting Budapest Bar Lamp Opal	LED / 8.5W / E27 Dimmable	-	3000K	Opal & Brass	Bar/ Table Mounted	Diameter - 290mm Height - 470mm Base Diameter - 195mm	Dimmable	
B2	Surface Mounted Lamp on Banquette	MG&Co Adjustable Brass Table Lamp Small Mrs Alice "Olive Lotus" Lampshade @ 22cm	LED / 4W / B22 Dimmable	-	3000K	Brass	Surface / Banquette Mounted	Ø170 x 400-600 Adjustable Height	Dimming via 5A socket lighting circuit	
B3	Free Standing Bedside Lamp	Client Supply							13A plug with switch on power cable	
B4	Free Standing Dimming Table Lamp	Client Supply							5A plug Dimming	
B5	Floor Standing Dimming Lamp	Client Supply							5A plug Dimming	
C1	Flush downlight Lamp	Felix Lighting Chrisholme Ceiling Light	LED / 2 x G9 / Dimmable	-	3000K	Bronze	Flush Mounted On Ceiling	Ø330 200H	Dimming	

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
P1A	Pendant Light in Bedrooms 3, 4, 5, 7	George Nelson Ball Crisscross Pendant Lamp Criss Cross Medium (48.5cm) 4882_24826	LED / 13W / E27 (not supplied with fitting) Dimmable	-	3000K	Silver Finish Ceiling Plate	Suspended	Cable max length 183cm reduced to suit room	Dimming	
P1B	Pendant Light in Bedrooms 1, 2	George Nelson Pear Crisscross Pendant Lamp Criss Cross Medium (43cm) 11544_61147	LED / 13W / E27 (not supplied with fitting) Dimmable	-	3000K	Silver Finish Ceiling Plate	Suspended	Cable max length 183cm reduced to suit room	Dimming	
P1C	Pendant Light in Bedrooms 9, 10, 11	Lindi Aged Brass And Linen Oversized Scalloped Pendant LL3010	LED / 13W / E27 (not supplied with fitting) Dimmable	-	3000K	-	Suspended	Cable max length 300cm reduced to suit room	Dimming	
P1D	Pendant Light in Bedroom 6	TBC by client		-	3000K	-	Suspended		Dimming	

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
P1F	Pendant Light in Bedroom 8	Lights & Lamps Ottino - Aged Brass And Linen Pendant LL3011	LED / 13W / E27 (not supplied with fitting) Dimmable	-	3000K	-	Suspended	Ø620 395H Cable max length 300cm reduced to suit room	Dimming	
P2	Small Pendant in Windows	The Wall Lighting Company Bodium Ribbed Glass Pendant Light - Small In Antique Brass PL-085-0012-AB	LED / 8W / B22 Dimmable	-	3000K	Antique Brass Finish Dark Brown Twistflex	Suspended	Ø155 110H Cord max length 1m reduced to suit room	Dimming	
P3	Large Pendant Wine Shop	The Wall Lighting Company Denton Ribbed Ceramic Pendant Light - Medium in Bronze PL-043-0002-BNZ	LED / 8W / E27 (not supplied with fitting) Dimmable	-	3000K	Antique Brass Finish Dark Brown Twistflex	Suspended	Ø190 120H Cord max length 1m reduced to suit room	Dimming	
P4	Suspended Pendant in Stairwell	Lights & Lamps Folia - Small Scalloped Natural Linen Pendant LL4012	LED / 13W / E27 (not supplied with fitting) Dimmable	-	3000K	Bronze	Suspended	Ø320 501H Cord max length 3m reduced to suit room	Dimming	

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
P5	Suspended Pendant in Reception	Lights & Lamps Folia – Oval Scalloped Natural Linen Pendant LL4011	LED / 4 x E14 (not supplied with fitting) Dimmable	-	3000	Bronze	Suspended	250H 950W 322D Cord max length 2m reduced to suit room	Dimming	
P6	Ceiling Mounted – GF Hallway	Lights & Lamps Folia - Scalloped Natural Linen Flush Pendant LL4010	LED / 3 x E27 (not supplied with fitting) Dimmable	-	3000	Bronze	Surface	Ø450 277H	Dimming	
RL1	Reading Light Rooms 1, 2	BTC Hector Bibendum Room 1 – Red flex Room 2 – Green flex	LED / 40W / E27 (not supplied with fitting) Dimmable	-	3000K	Room 1 – Red flex Room 2 – Green flex	Wall Mounted	215H 210D 130W	Dimming	
T1	Track mounted Spotlight in Wine Shop	Cano Long Black for Multi Circuit Track MLS 3CCANO-LB Dimmable	LED / 5W / GU10	470lm	3000K	Black	Track Mounted on 3 Circuit Track (Eutrack)	Ø60 x 102L	To include lengths of 3 circuit track as per drawings Dimmable	
LB1	Linear LED Lightbar	Dextra GRD L45 OPTPA	LED/ 26W	3521lm	4000K	White	Surface Mount	1.5m		

Light Fitting Schedule

Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
LB1E	Linear LED Emergency Lightbar	Dextra GRD L45 LE3 OPTPA	LED / 26W	3521lm	4000K	White	Surface Mount	1500L x 215W x 82H	Integral 3 Hour Emergency Battery	
LB2	Linear LED Lightbar	Dextra GRD L45 LE3 OPTPA	LED / 26W	3521lm	4000K	White	Surface Mount	1500L x 215W x 82H	Integral Reacta R25E Sensor	
LB3	Linear LED	Hacel Infinitas Direct Surface Medium Output	LED / 24W	4050lm	3000K	White	Surface	1680L x 92W x 122H	Medium Output Switch Dim End cap cable entry	
EX1	External Lantern	The Limehouse Lamp Company LTD Chelsea Short Pillar Lamp Old Antique (ANT) IP44 433SP	1 x 100W ES, 1 x 25W G9	-	3000K	Old Antique (ANT)	Base Mounted On Wall Post	545H 230W 230D	IP44	
EX2	Shielded, circular wall-mounted bulkhead Car Park lights	David Hunt Lighting Strait Outdoor Wall Light Antique Brass IP44 STR1575	LED / 7W / GU10	-	3000K	Antique Brass	Wall Mounted	86D 108H 96W	IP44	

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
EX3	Surface Mounted External Wall Light	Limehouse Lamp Company Strathmore Slim Wall Lantern (Small) Old Antique (ANT) IP44 462S	LED / 25W / G9	-	3000K	Old Antique (ANT)	Surface Mounted	310H 110W 150D	IP44	
EX4	Surface Mounted External Lantern	The Limehouse Lamp Company LTD Chelsea Overhead Arm Old Antique (ANT) IP44 433O ANT IP44	1 x 100W ES, 1 x 25W G9	-	3000K	Old Antique (ANT)	Wall Mounted	300H 230W 410D	IP44	
EX5	Surface Mounted External Linear	Ansell Lighting Tornado Pro 1800 Microwave Sensor ATORPLED6/MWS	LED / 36W	3700	4000K	Grey	Surface Ceiling	1865L 85W 70D	IP65 Microwave Sensor	
EX6	Surface Mounted External Lantern	DW Windsor WIU Performance CoB	TBC	TBC	3000K	RAL 9005 Black	Wall Mounted – Ornate Cast Wall Box Bracket	440W 440D 883H	IP66 Miniature Photocell 20 lux	
EL1-RO	Standalone Emergency Light Recessed Open Area Optic	Thorlux Firefly SmartScan	3W Open Area Optic	270lm	-	White Recess Trim	Recessed	Ø70 x 21	Open Area Optic Non-maintained SmartScan Emergency 3-hour Emergency Duration 3 W Eco-Power Pack PP17402	

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
EL1-RC	Standalone Emergency Light Recessed Corridor Optic	Thorlux Firefly SmartScan	3W Corridor Optic	270lm	-	White Recess Trim	Recessed	Ø70 x 21	Corridor Optic Non-maintained SmartScan Emergency 3-hour Emergency Duration 3 W Eco-Power Pack PP17402	
EL1-SO	Standalone Emergency Light Surface Mount Open Area Optic	Thorlux Firefly Surface Round Body SmartScan	3W Open Area Optic	270lm	-	White (RAL 9016)	Surface	245 x 155 x 39	Open Area Optic Non-maintained SmartScan Emergency 3-hour Emergency Duration	
EL1-SC	Standalone Emergency Light Surface Mount Corridor Optic	Thorlux Firefly Surface Round Body SmartScan	3W Corridor Optic	270lm	-	White (RAL 9016)	Surface	245 x 155 x 49	Corridor Optic Non-maintained SmartScan Emergency 3-hour Emergency Duration	
EL2-S	Wall Light Stairs Emergency	Thorlux Lighting Celo	LED / 2W	180	3000K		Wall Mounted	252L x 78W x 160H	Integral LED Non-maintained SmartScan Emergency 3-hour Emergency Duration	
EL3X-S	Wall Light External Emergency Standalone	Kingfisher SEMITA Urban Flood Optic FL SEMUFL15D27K	LED / 11W	1530	2700K	Allow for custom RAL colour TBC by client/architect	Wall Mounted 400 FFL	337W 148H 82D	Integral LED Non-maintained 3-hour Emergency Duration Flood Optic FL IP66	

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06

Corsham House Hotel

Architect: Ian Hopwood - Ian Hopwood
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
EL-GW	Emergency Lighting Gateway Located in GF Reception Cupboard	Thorlux SmartScan Gateway	-	-	-	-	Wall Mounted	158W 275H 50D	1No. required for full SmartScan system	
EL-CC	Emergency Lighting Conversion Kit	Liteplan Emergency LED Strip BMM/1/MinEM/SPC Contact Steve Green Liteplan Limited m: +44 (0) 7778 030680 Steve.Green@liteplan.com	5.7	300	-		LED strip to be mounted to top inside face of fitting EX4.	LED Strip Dimensions 52L 8W Battery Dimensions 90L 24W 28H Module Dimensions 135L 30W 21H	Driver and battery to be installed internally within managers station To be provided with connector block to allow cable to LED strip to be extended on site to connect between internal and external components	
ES1-R	Exit Sign Recessed	Thorlux Lex SmartScan	1W	-	-	White (RAL 9016)	Semi Recessed Mounting Kit LEX20167	320 x 82 x 178	Maintained SmartScan Emergency 3-hour Emergency Duration 19.5m viewing distance	
ES1-S	Exit Sign Surface Mount	Thorlux Lex SmartScan	1W	-	-	White (RAL 9016)	Surface Mount	320 x 82 x 178	Maintained SmartScan Emergency 3-hour Emergency Duration 19.5m viewing distance	

Corsham House Hotel

Architect: **Ian Hopwood - Ian Hopwood**
Issue Status: Issued for Construction

REF	DESCRIPTION	MANUFACTURER / MODEL / REF	LAMP / POWER / CAP	INITIAL LUMENS	COLOUR Ra/TEMP K	TRIM / FINISH / ACCESSORIES	MOUNTING DETAILS	DIMENSIONS (LxWxH OR dia.xH) mm	NOTES	IMAGE
ES1-W	Exit Sign Wall Mount	Thorlux Lex SmartScan	1W	-	-	White (RAL 9016)	Wall Mounting Kit LEX13391W9	320 x 82 x 178	Maintained SmartScan Emergency 3-hour Emergency Duration 19.5m viewing distance	

Notes

- Contractor to ensure that the catalogue number is consistent with the description prior to order.
- Contractor to ensure that quantities of equipment are consistent with Architects layout.
- All items identified as ‘contractor to choose’ – contractor required to submit proposals to the Architect/Engineer a minimum of 2 weeks prior to placing an order.
- All connected non-linear loads below 16A per phase (3.7kW single phase, 11kW three phase) must comply with the harmonic emission limits given in BSEN:61000-3-2.
- All connected non-linear loads above 16A per phase (3.7kW single phase, 11kW three phase) must comply with the harmonic emission limits given in BSEN:61000-3-4.
- Emergency conversion is to be carried out in accordance with ICEL 1004 by an approved supplier, to comply with BS EN 60598-2-22:1999.
- All light fittings and gear must have a minimum power factor of 0.9.
- Contractor to provide samples of all fittings
- All Lighting control gear / ballasts to operate safely on 230V +10%/-6% unless otherwise indicated. Contractor to verify & confirm compliance prior to ordering & installation on site.

Rev	Date	Status	Description	Engineer	Project Leader
P01	05/06/2023	S2 – For information	DRAFT for Information	RHB	IEJ
P02	16/07/24	A4	Issued for Construction	JF	IEJ
P03	07/11/24	A4	Issued for Construction	JF	IEJ
P04	09/09/25	A4	Issued for Construction	JF	IEJ
P05	17/06/25	A4	Issued for Construction	JF	IEJ
P06	20/08/25	A4	Issued for Construction	JF	IEJ
			- EL1-SO and EL1-SC surface mount emergency lights changed to round body		
			- EX6 added		

Light Fitting Schedule
Dwg #: J7165-MXF-XX-XX-SH-E-30000 Rev P06