






# LEFORT GEOPHYSICS

## Land East of Ashley Coombe Warminster, Wiltshire

### Gradiometer Survey Report



Report Ref: 25-0023.01

October 2025



**Land East of Ashley Coombe,  
Warminster, Wiltshire**

**Gradiometer Survey Report**

Prepared for:  
**Landgage Heritage**  
Unit 2a Chanctonfold Estate  
Horsham Road  
Steyning  
West Sussex  
BN44 3AA



Prepared by:  
**Lefort Geophysics**  
The Old Vicarage  
83 Fore Street  
North Petherton  
Somerset  
TA6 6QA

*Author:*  
Ross Lefort

*Document Version:*  
Version 1 (Draft)

*Site Centre Point:*  
NGR 387100, 143900

**October 2025**

**Report Reference: 25-0023.01**

**Disclaimer**

The material contained in this report and accompanying figures has been produced for an individual client. This report and accompanying figures is not intended for use by any third party and Lefort Geophysics will not be responsible, as far as the law allows, for any damage or loss sustained to such third parties relying on information in this report.



# Land East of Ashley Coombe, Warminster, Wiltshire

## Gradiometer Survey Report

### Contents

|                                                                           |    |
|---------------------------------------------------------------------------|----|
| Summary .....                                                             | ii |
| Acknowledgements .....                                                    | ii |
| 1. Introduction.....                                                      | 1  |
| 1.1. Project Background and Survey Objectives.....                        | 1  |
| 1.2. Site Location and Topography .....                                   | 1  |
| 1.3. Geology and Soils .....                                              | 2  |
| 1.4. Archaeological and Historical Background .....                       | 2  |
| 2. Methodology.....                                                       | 3  |
| 2.1. Introduction.....                                                    | 3  |
| 2.2. Method .....                                                         | 3  |
| 3. Results and Interpretation .....                                       | 4  |
| 3.1. Introduction.....                                                    | 4  |
| 3.2. Gradiometer Survey Results and Interpretation.....                   | 4  |
| 3.3. Gradiometer Survey Results and Interpretation: Modern Services ..... | 5  |
| 4. Conclusions.....                                                       | 7  |
| 5. References .....                                                       | 8  |
| 5.1. Bibliography.....                                                    | 8  |
| 5.2. Cartographic Sources .....                                           | 8  |
| 5.3. Wiltshire Historic Environment Records Consulted .....               | 8  |
| APPENDIX 1: THEORY, SURVEY STRATEGY AND DATA PROCESSING .....             | 9  |
| Basic Theory .....                                                        | 9  |
| Detailed Survey Methodology .....                                         | 10 |
| Data Processing Methodology .....                                         | 11 |
| APPENDIX 2: INTERPRETATION CATEGORIES.....                                | 12 |

### Figures

- Figure 1: Site location and gradiometer survey extents
- Figure 2: Greyscale plot
- Figure 3: XY trace plot
- Figure 4: Interpretation
- Figure 5: Greyscale plot (unprocessed raw data)



---

## **Land East of Ashley Coombe, Warminster, Wiltshire**

### **Gradiometer Survey Report**

#### **Summary**

A gradiometer survey was conducted over land off Ashley Coombe, some 1.25km SSW of the centre of Warminster, Wiltshire. The project was commissioned by Landgauge Heritage with the aim of establishing the presence, or otherwise, and nature of detectable archaeological features on the site ahead of proposed development.

The site is located on the eastern end of a WNW-ESE aligned ridge on the southern edge of Warminster, some 7.25km south of the centre of Westbury. The survey area measures approximately 7.11ha and of this a total of 6.49ha has been covered by geophysical survey.

A clear settlement enclosure with at least one visible ring ditch inside was detected in the southern third of the dataset. Broad, shallow ditches or trackways cross the southern two thirds of the dataset and may run towards a former quarry. Other potential archaeological features include the fragmentary remains of an earlier field system.

The other responses detected include numerous agricultural features, geological variations, trends of uncertain origin and at least three modern services.

The survey was undertaken by the Lefort Geophysics survey team in two phases between the 19<sup>th</sup> of May and the 23<sup>rd</sup> of September 2025.

#### **Acknowledgements**

The gradiometer survey was commissioned by Landgauge Heritage. The assistance of William Bedford, James McNicoll-Norbury and Charlie Winterburn is gratefully acknowledged in this regard.

The fieldwork was undertaken by Ross Lefort who processed and interpreted the geophysical data in addition to producing this report.



# Land East of Ashley Coombe, Warminster, Wiltshire

## Gradiometer Survey Report

### 1. Introduction

#### 1.1. Project Background and Survey Objectives

- 1.1.1. Lefort Geophysics was commissioned by Landgage Heritage to carry out a geophysical survey over land off Ashley Coombe, on the southern edge of Warminster, Wiltshire. The survey area is centred on NGR 387100, 143900 (**Figure 1**).
- 1.1.2. This survey forms part of a wider scheme of works being undertaken in advance of proposed development at the site. The area selected for geophysical survey measures approximately 7.11ha.
- 1.1.3. The following aims have been set out for the geophysical survey:
  - *To conduct a gradiometer survey that covers as much of the specified area as possible, allowing for surface obstructions.*
  - *To determine the presence or absence of archaeological features, as far as the technique and site conditions will allow, and to map the extent of any features that may be present.*
  - *To clarify the general nature and possible significance of the detected features.*
  - *To produce a report of the survey results in sufficient detail to support an informed decision as to the site's archaeological potential.*
- 1.1.4. This report sets out details of the site's location, the methodology followed, the survey results and the archaeological interpretation of the geophysical data.

#### 1.2. Site Location and Topography

- 1.2.1. The site is located approximately 1.25km SSW of the centre of Warminster and some 7.25km south of the centre of Westbury, Wiltshire. The site comprises part or all of three pasture fields with the survey extents defined by existing property boundaries to the north, west and south and the limits of the proposed development along the eastern edge (**Figure 1**).
- 1.2.2. The site spans the eastern end of a WNW-ESE aligned ridge. The southern half of the survey area slopes gently downwards towards the ESE from a height of over 140m above Ordnance Datum (aOD) in the centre of the site to under 135m aOD at the southern tip of the site. A dry valley runs through the northern half of the dataset towards the ENE with the land falling from over 135m aOD to under 115m aOD at the northern tip of the site.
- 1.2.3. An unnamed stream is located outside the site near the northern tip. This stream flows southeast towards the River Wylfe that passes the site to the east. The River Wylfe flows north before turning and flowing towards the east.



### **1.3. Geology and Soils**

- 1.3.1. The bedrock geology under the site is recorded as sandstone deposits of three different formations that all date to the Cretaceous Period. The southern higher ground is recorded as Boyne Hollow Chert Member, the northern majority is recorded as Shaftesbury Sandstone Member and the sandstone under the northern tip is recorded as Cann Sand Member. No superficial deposits have been recorded under the site (BGS 2025).
- 1.3.2. The soils underlying the site are recorded as typical brown earths of the 541B (Bearsted 2) association (SSEW 1983).
- 1.3.3. It is considered that soils derived from the parent material outlined above can produce contrasts suitable for the detection of archaeological features through geophysical survey.

### **1.4. Archaeological and Historical Background**

- 1.4.1. The following information is summarized from the online database for the Wiltshire HER (<https://services.wiltshire.gov.uk/HistoryEnvRecord/Home/Index>) (Historic Environment Record). A search was performed for all heritage assets within 1km of the site with the most relevant records discussed below.
- 1.4.2. The only record located within the survey area relates to two undated narrow ditches (ST84SE641). An undated bank lies further down the hill, outside of the area surveyed (ST84SE642).
- 1.4.3. Two Neolithic pits were discovered during an evaluation carried out to the northeast of the site. One pit was found to contain Early Neolithic pottery with the other containing worked flint (MWI75280 and MWI75282).
- 1.4.4. An undated ring ditch, pits and ditches were identified through geophysical survey to the WSW of the site (MWI78252, MWI78253 and MWI78254).
- 1.4.5. The remaining nearby records relate to medieval and post-medieval agricultural use of this area. A number of outfarm and farmsteads are recorded in the vicinity with Butler's Coombe Farm being the closest. This is recorded as a partially extant 18<sup>th</sup> century farmstead (MWI71491).



## 2. Methodology

### 2.1. Introduction

- 2.1.1. Magnetometer survey was selected for the investigation of this site as this was deemed to be the most appropriate technique for the rapid assessment of a site in this geological setting. The survey was carried out using a Bartington Grad601-2 dual fluxgate gradiometer and was conducted in accordance with guidelines set by Historic England (2008) and the Europae Archaeologiae Consilium (EAC 2016).
- 2.1.2. The survey was undertaken by the Lefort Geophysics survey team in two phases between the 19<sup>th</sup> of May and the 23<sup>rd</sup> of September 2025. Site conditions were good during both phases of the survey with low vegetation, firm ground under foot and a slightly varying surface temperature due to the partly cloudy conditions. Of the proposed 7.11ha area a total of 6.49ha was covered by geophysical survey. The slight shortfall in coverage is due largely to areas of overgrowth along the north edge of the northern field.

### 2.2. Method

- 2.2.1. The survey grid nodes were established at 30m x 30m intervals using a Leica Viva RTK GNSS instrument. Positional corrections are provided for this system by SmartNet which gives a precision of approximately 0.03m and therefore exceeds the Historic England and EAC minimum requirements for geophysical survey (English Heritage 2008 and EAC 2016).
- 2.2.2. The Bartington Grad601-2 gradiometer system has two sensor tubes set at a horizontal separation of 1m; this allows for two lines of data to be collected simultaneously. The upgraded system has an effective sensitivity of 0.03nT. Data were collected at 0.25m intervals along transects spaced 1m apart using the zigzag method. This survey strategy is in accordance with Historic England's minimum requirements and conforms to a Level 1 (prospection) survey, as defined by the EAC (2016).
- 2.2.3. The survey data were subject to minimal correction processes using Geoplot and in-house software. The processing functions used include:
- Group Zero Median Traverse (GZMT): This was applied to remove minor variations between the two Bartington sensors. This method of processing prevents the removal of archaeological features that run in-line with the traverse direction. Thresholds of  $\pm 5\text{nT}$  were applied.
  - Zero Median Traverse (ZMedT): This was applied to all grids to remove minute variations between the two Bartington sensors left behind by GZMT. Thresholds of  $\pm 1\text{nT}$  were applied.
  - Zero Mean Traverse (ZMT): This was applied to grids dominated by ferrous responses where GZMT failed to remove sensor variations. Thresholds of  $\pm 5\text{nT}$  were applied.
  - Deslope: This was used on selected grids to correct minor grid edge discontinuities introduced by earlier processing steps.
  - Destagger: This corrects small errors in traverse position introduced by varying topography and ground cover.
- 2.2.4. Further details of the survey equipment, fieldwork procedures and methods of processing are described in **Appendix 1**.



### 3. Results and Interpretation

#### 3.1. Introduction

- 3.1.1. The gradiometer survey has been successful in identifying a number of anomalies of likely and possible archaeological interest. A number of other features have been detected including numerous agricultural features and at least three modern services. Results are presented as a series of greyscale plots, XY trace plots and archaeological interpretations at a scale of 1:1500 (**Figures 2 to 4**). The greyscale plots are displayed from -2nT (white) to +3nT (black) and the XY trace plots are displayed at  $\pm 25$ nT at 25nT per cm.
- 3.1.2. A greyscale plot of the raw data is included as an appendix figure which is displayed from -5nT to +5nT (**Figure 5**).
- 3.1.3. The interpretation of the dataset highlights the presence of potential archaeological features, modern features, geological responses, agricultural features and anomalies of uncertain origin (**Figure 4**). Full definitions of the interpretation terms used in this report are provided in **Appendix 2**.
- 3.1.4. Numerous ferrous responses have been observed throughout the gradiometer dataset. These are presumed to be modern and are not referred to, unless they are considered relevant to an archaeological interpretation.

#### 3.2. Gradiometer Survey Results and Interpretation

- 3.2.1. Part of a large enclosed settlement has been detected in the southern third of the dataset. It is defined by weakly positive ditches at **1001** to **1003** and measures at least 165m in length with a minimum width of 130m. The enclosure likely continues to the east and south of the area surveyed. The weak magnetic values suggest either the ditch does not contain a large amount of magnetised material or that the ditch is shallow.
- 3.2.2. The interior appears to have a larger concentration of pits and ditches in the northern end of the enclosure, on the higher ground. A likely ring ditch is visible around **1004** and has an internal diameter of 18m. It appears to have an opening on its southeast side.
- 3.2.3. A horseshoe arrangement of pits is located to the northwest of this ring ditch, around **1005**, with a weak internal dividing ditch close by at **1006**. A number of pit clusters and ditch-like responses are located across the northern end of the enclosure at **1007** to **1010**.
- 3.2.4. The western side of the interior is divided into small, mostly empty enclosures by ditches at **1011** to **1014**. The northernmost of these ditches curves towards the ring ditch leaving a small access gap in between. This suggests the internal dividing ditches and the ring ditch may be contemporary.
- 3.2.5. The remaining area of the southern interior contains far fewer archaeological features. This may suggest this area of the interior served a more agricultural function but could also be related to this steeper area being more prone to erosion and plough damage.



- 3.2.6. The features outlined above are all classed as either archaeology or possible archaeology. Features classed as possible archaeology either have very weak magnetic values, diffuse edges or are closely associated with ferrous responses.
- 3.2.7. Two alignments of ditches or deeply rutted trackways run though the site at **1015** to **1020** that converge at **1021**. These appear to lead to an area at **1022** that is defined as superficial geology with spreads of increased magnetic response within. It is possible this area may prove to be a disused quarry. The linear responses leading to this possible quarry could relate to a broad and shallow ditch or could be the shallow fill of deeply rutted trackway. The magnetic values of these features varies along its length; stronger areas are classed as archaeology, weaker areas as possible archaeology and the very weakest sections as trends.
- 3.2.8. Ditches running on a NNW-SSE alignment are visible in the central third of the dataset at **1023** to **1025**. These could relate to the fragmentary remains of a field system and are classed as possible archaeology due to their weak magnetic values.
- 3.2.9. Further ditches are visible at **1026** and **1027** that run on a rough southwest-northeast alignment. These may also define undated field system remnants and are classed as possible archaeology.
- 3.2.10. A former field boundary is visible at **1028** that is marked on the 1887 edition Ordnance Survey map. A possible unmapped boundary appears to cross the interior at **1029** to **1031** that appears to run to a wooden pylon at **1030**. Given the close proximity of the pylon, it could be argued these features may relate to modern services.
- 3.2.11. Some other ditches at **1032** and **1033** are aligned parallel and perpendicular to a nearby quarry marked on the 1887 edition Ordnance Survey map. These could either relate to the quarry or are contemporary agricultural ditches.
- 3.2.12. A clear modern service crosses the dataset at **1034** with interference from overhead power cables visible at **1035** to **1036**. These responses will be discussed in the next section of the report.
- 3.2.13. Broad variations in the magnetic background in the northern third of the dataset have been interpreted as superficial geology around **1022**, **1037** and **1038**.
- 3.2.14. The remaining responses have been classed as trends of uncertain origin. Some, such as at **1039**, may prove to be of archaeological interest whereas others, such as around **1040**, may prove to be agricultural or geological in origin.

### **3.3. Gradiometer Survey Results and Interpretation: Modern Services**

- 3.3.1. A modern service crosses the dataset at **1034**. A line of disturbance highlighted as increased magnetic response at **1035** and **1036** is caused by overhead power lines that run close to the ground surface near the ridge top.
- 3.3.2. While not presenting in the data as a clear service, it could be argued that the ditches at **1029** to **1031** could prove to be related to modern service trenches. They both run from a wooden pylon and may be related to the power network.



- 
- 3.3.3. It is not clear if any of the detected services are in active use. It should also be noted that gradiometer data will not be able to detect all services on site. Services made from non-ferrous material are unlikely to generate the distinctive response that would allow for a classification as a service. Plastic pipes are particularly hard to detect for example.
- 3.3.4. This report and accompanying illustrations should not be used as the sole source for service locations. Service maps should be consulted in addition to employing appropriate equipment (e.g. CAT and Genny) to confirm service locations before any invasive activities are carried out on site.



## 4. Conclusions

- 4.1.1. The gradiometer survey has been successful in identifying anomalies of likely and possible archaeological interest. A number of other features have been detected including numerous agricultural features and at least three modern services. The survey and this report are considered to have addressed all of the aims set out for the project.
- 4.1.2. The settlement enclosure detected in the southern third of the dataset is the most noteworthy group of features observed. The higher northern end of this enclosure appears to have the highest concentration of archaeological features and may have been the main settlement area. The southern half is relatively sparse and may have served a more agricultural function. The one ring ditch detected most likely represents a roundhouse although it seems to be the only clear example of one within the interior.
- 4.1.3. The shallow ditches or trackways that cross the southern two thirds of the dataset appear to cut through the settlement enclosure in places so may not be contemporary. These features may have once run to a quarry.
- 4.1.4. There are faint traces of possible field systems that run on a differing alignment to nearby modern boundaries. These may represent the fragmentary remains of earlier field systems of unknown date.
- 4.1.5. The scattered pit-like responses, outside of the settlement enclosure, are regarded as having a low archaeological potential. This is due to the close proximity of many of these responses to larger ferrous anomalies that could be responsible for creating them coupled with the possibility that many may prove to be natural features such as tree throws.
- 4.1.6. The majority of detected features attest to this area serving an agricultural function along with some rural industrial function in recent centuries.
- 4.1.7. Gradiometer survey has a proven track record of identifying a wide range of archaeological features in a diverse range of geological settings. It is however a possibility that other archaeological features may exist that are not detectable through gradiometer survey. Stone walls composed of a sedimentary rock, for example, may not be visible on a site with similar underlying geology as there is no measurable magnetic contrast between the wall and the surrounding soil. Inhumation burials are also difficult to identify at times as the backfill of the grave is largely unchanged, in terms of its magnetic properties, during the burial process.
- 4.1.8. The dimensions of the modern services in the gradiometer data are indicative of the strength of their magnetic response; this varies according to the materials used in their construction. The physical extents of the services may therefore differ in the ground from that depicted in the geophysical data. It is not possible to accurately determine the depth of burial of these services through gradiometer survey.



---

## 5. References

### 5.1. Bibliography

EAC. 2016. *EAC Guidelines for the Use of Geophysics in Archaeology: Questions to Ask and Points to Consider (EAC Guidelines 2)*.

English Heritage. 2008. *Geophysical Survey in Archaeological Field Evaluation. Research and Professional Service Guideline*. No 1, 2<sup>nd</sup> edition.

### 5.2. Cartographic Sources

British Geological Survey (BGS). 2025. *Geology of Britain Viewer* [Online]. Available at: <https://geologyviewer.bgs.ac.uk/> [Accessed: 02/10/2025].

Ordnance Survey. 1887. *Wiltshire, Sheet LI.12 (1:2500)*. Ordnance Survey: Southampton.

Soil Survey of England and Wales (SSEW). 1983. *Sheet 5: Soils of South West England*. Ordnance Survey: Southampton.

### 5.3. Wiltshire Historic Environment Records Consulted

MWI71491 – Butler's Combe Farm.

MWI75280 – Neolithic Pit.

MWI75282 – Neolithic Pit.

MWI78252 – Undated Ring Ditch, Bore Hill Farm.

MWI78253 – Undated Ditches, Bore Hill Farm.

MWI78254 – Undated Pits, Bore Hill Farm.

ST84SE641 – Ditches, Henford Marsh.

ST84SE642 – Undated Bank, Henfords Marsh.



## APPENDIX 1: THEORY, SURVEY STRATEGY AND DATA PROCESSING

### Basic Theory

#### Introduction

The two geophysical survey techniques carried out by Lefort Geophysics are magnetometer and earth resistance survey. Magnetometer survey is routinely used for archaeology due to the rapid area coverage achievable, in addition to its successful track record in many different geological settings. Earth resistance survey is slower by contrast, but can reveal archaeological features that may be missed by a magnetometer survey.

#### Magnetometer Survey

This technique involves measuring minor variations in the Earth's magnetic field; these variations are caused by a number of human induced and natural phenomenon. Humans can enhance the magnetic properties of soils in a number of ways; such as through the creation of ceramic/metallic objects, deposition of settlement waste and through burning. The resulting enhanced soils that fill pits and ditches make these features detectable.

Some natural phenomenon, like underlying geology and the sun, create large scale magnetic variations that can mask weaker archaeological features. A common way of filtering out these large scale effects is to collect data using two magnetometer sensors, one mounted at a fixed distance above the other. The lower sensor is closer to the ground and is therefore more sensitive to shallow, small scale changes; both sensors measure the large scale variations to a similar degree. When data from one sensor is subtracted from the other, the effect is to remove the large scale variations to reveal a clear picture of potential archaeological features. This configuration is known as a gradiometer and the system used by Lefort Geophysics works in this way.

There are several different types of magnetometer sensor available but the two most commonly used for archaeology are fluxgate and caesium vapour. The basic difference between the two is that caesium vapour measures the total strength of the magnetic field whereas fluxgate only measures a component of the field in a particular direction.

The advantages of the fluxgate sensors are their robust and lightweight design coupled with a lower power consumption; these factors make for an excellent piece of field equipment. Caesium vapour magnetometers are considered to be more sensitive with a lower noise level. In most cases this difference in sensitivity and noise is not enough to warrant use of caesium vapour over fluxgate sensors. Use of caesium vapour sensors is considered most advantageous when searching for deeply buried archaeological features.

#### Earth Resistance Survey

Earth resistance survey works, in simple terms, by passing a weak electrical current through the soil and measuring variations in electrical resistance. Resistance varies according to differences in soil moisture content and by the presence of materials of varying resistivity. A wall, for instance, is likely to be dry and composed of poor conducting materials; this results in a high measured resistance value. A ditch filled with wetter, better conducting material will register a lower resistance value by contrast.

Four electrodes are used to measure resistance, two pass a fixed electric current through the ground (current probes) and the other two sample the voltage required to drive this current (voltage probes). The variations in voltage required to drive the current are indicative of the varying electrical resistance. The four electrodes can be arranged in a



variety of different configurations, the twin-probe array is the widest used of these. The twin-probe involves grouping the four electrodes into two pairs, with a current and voltage probe in each pair. The pairs are separated by a large distance with one set in a fixed position and the other moved across the survey area to sample the varying resistance.

In general terms, the wider the electrode spacing, the deeper the technique can penetrate. The catch is that a wider electrode spacing increases the volume of soil sampled. This can result in smaller features, such as internal walls, being less detectable when investigating to greater depths. The standard probe separation used for commercial archaeology is 0.5m and this is considered suitable for the investigation of most rural sites in Britain.

The main weakness of earth resistance survey is that the quality of results are dependent on climatic conditions on the day and in the weeks running up to the survey. If the site is waterlogged then there is little contrast, the same is true if the site is too dry. This constraint puts the technique at a disadvantage in the commercial sector where waiting for the right conditions is not always possible.

### Detailed Survey Methodology

Magnetometer data is collected using a Bartington Grad601-2 dual fluxgate gradiometer system. This has two sensor tubes mounted at a horizontal separation of 1m which allows for the simultaneous collection of two transects of data. Each sensor tube contains two fluxgate sensors arranged as a vertical gradiometer at a separation of 1m. This system can suppress large scale variations that might obscure potential archaeological features.

The Bartington Grad601-2 has an effective sensitivity of 0.03nT when set at a range of  $\pm 100$ nT in grid mode. The standard resolution for a geophysical survey is to collect readings at 0.25m intervals along transects spaced 1m apart. Data is collected in grids measuring 30m x 30m and at the resolution outlined above results in 3600 readings per grid. Higher sample density surveys can be carried out at a 0.125m separation along transects spaced 0.25m apart. This results in 28800 readings per 30m grid.

Magnetometer data can also be collected using a cart system. On this system multiple Bartington Grad601-2 can be mounted with positions logged by a Trimble base and rover GPS system. The advantage of using this system is that each reading has greater positional accuracy compared to grid based data collection. The Trimble 5800 system is capable of a horizontal accuracy of  $\pm 1$ cm and a vertical accuracy of  $\pm 2$ cm.

The earth resistance data is collected using a Geoscan Research RM15 system using the twin-probe array. The mobile electrodes are mounted on a fixed bar with a multiplexer (MPX15) used to allow two transects of data to be collected simultaneously. A probe separation of 0.5m is typically used with data collected at 1m intervals along transects spaced 1m apart, in line with English Heritage minimum requirements.

The 30m x 30m survey grid nodes and base points for the Trimble 5800 system are accurately established in the field using a Leica Viva series RTK GNSS instrument. This system achieves a high level of precision thanks to a network of reference stations operated by the Ordnance Survey and Leica Geosystems, known as SmartNet. These reference stations provide positional corrections that are fed to the system via a mobile internet connection. This enables the system to achieve an accuracy of 0.03m which exceeds the English Heritage minimum requirements (2008).



## Data Processing Methodology

The collected gridded gradiometer data are downloaded from the Bartington system using the software provided. Data are saved in a Z format with a separate header file generated for survey parameters. Data are then imported into the processing software Geoplot to correct minor errors. These corrections aim to enhance the results for greater clarity. The processing applied is minimal with no filtering or interpolation used.

The processing steps for gridded data include Group Zero Median Traverse (GZMT) followed by a narrow threshold Zero Median Traverse (ZMedT). This method of processing allows variations between the Bartington sensors to be removed while minimising the potential loss of features that run in line with traverse direction. Other processing steps include deslope, and destagger with Zero Mean Traverse (ZMT) applied to selected ferrous dominated grids.

GZMT works by grouping the 30 traverses of data into four groups according to the sensor used and its orientation during data collection. The median values of each line of data are calculated and from these results an overall median value for each of the four groups is calculated. These four values are used to correct each of the 30 traverses. This is then followed up with ZMedT; this removes minor variations that are a result of instrument drift and preserves archaeological features thanks to a very narrow threshold.

The ungridded magnetometer cart data are downloaded from the acquisition software Nav601 and positions for each reading are calculated in Trackmaker601. This results in an XYZ file of the magnetometer data that can be processed. Gridded data is processed in MagPick to remove variations between Bartington sensors. The most common processing applied is a linear filter to remove variations between sensors.

The earth resistance data are downloaded in Geoplot in the .grd file format. Minor data corrections are then applied in Geoplot. The main difference from the processing of gradiometer data is that filtering is applied to earth resistance data.

The typical processing steps applied to earth resistance data are as follows:

- Despike: Removes anomalous data points that can arise during data collection.
- Edge Match: Corrects for differences between grids that arise when survey is carried out on different days or through the movement of the fixed probes.
- Multiply: This multiplies data in a selected area by a specified positive or negative value and alongside edge match is useful for the correction of grid differences.
- Low Pass Filter: This is used to remove small scale spatial detail and is useful for enhancing broad, weak anomalies.
- High Pass Filter: This removes large scale spatial detail and is useful for filtering out broad geological responses that could obscure archaeological features.

Two methods of data display are used to show gradiometer data: greyscales and XY trace plots. For the display of earth resistance data greyscale plots are used only.

- Greyscale: Presents the data in plan view with a shade of white, grey or black assigned to each reading according to its magnetic or resistance value. At the standard survey resolution each rectangular pixel corresponds to a reading.
- XY Trace: Presents each line of the magnetic data as a graph line with multiple lines overlapping to produce a stack of profiles. The graph running upwards signifies a positive anomaly (red) and running down (black) indicates a negative. This is of help in further characterising a magnetic anomaly as either archaeological or ferrous.



## APPENDIX 2: INTERPRETATION CATEGORIES

The interpretation methodology used by Lefort Geophysics divides anomalies into five main categories: archaeological, agricultural, modern, geological and uncertain origin.

The archaeological category is used where a detected anomaly presents a shape or configuration that looks to be indicative of a buried archaeological feature. Further sources of information including aerial photography and historic maps may be incorporated into the final interpretation. This category is sub-divided into two groups based on levels of confidence in the interpretation.

- Archaeology – this is used to classify anomalies with a clear anthropogenic pattern that do not appear to relate to modern or agricultural features.
- Possible Archaeology – this is used for anomalies that give a fairly regular pattern but cannot be discounted as relating to modern, agricultural or geological features.

The modern category is used for anomalies that are presumed to be relatively recent in date. Modern is sub-divided into two categories as follows:

- Ferrous – used for anomalies characterised by a dipolar or bipolar response. Such anomalies can be caused by the presence of iron and ceramic material and are assumed to be modern in origin.
- Modern Service – used for responses considered to correspond to buried pipes and cables. Most detectable services are made from ferrous or ceramic materials.

The agricultural category is sub-divided into five categories as follows:

- Former Field Boundary – used for anomalies that are shown to correspond to the positions of field boundaries marked on historic maps.
- Agricultural – used for anomalies that follow known agricultural features or run parallel to them but do not appear on historic mapping.
- Ridge and Furrow – these are defined by broad and diffuse linear positive and negative anomalies. Ridge and furrow are broad strips of raised ground with parallel ditches that were cultivated during the medieval and post-medieval periods.
- Ploughing – used to define narrow linear trends running through the data created by ploughing scars in the soil.
- Drainage – used to define ceramic field drains or ditches running through a field that are used to keep the soil well drained. Ceramic drains are identified by their distinctive anomaly form whereas ditched drains are identified more by their layout.


The geological category defines areas of broad and diffuse responses that are not considered to be archaeological. There are two sub-divisions of this category:

- Superficial Geology – used to define broad spreads of responses considered to relate to shallow geological deposits.
- Palaeochannel – used to define linear and curvilinear anomalies that are considered to represent former watercourses.

The uncertain origin category is used for anomalies that cannot be classified confidently in any of the four categories outlined above. There are two sub-divisions of this category:

- Increased Magnetic Response – used to define areas of varying magnetic responses.
- Trend – weak narrow linear responses that do not seem to relate to ploughing.

Other categories may be added in some instances to account for unusual features or where a project specification requires more detailed interpretation. Any additions will be outlined in the introduction of the results section of the survey report.



Site location and gradiometer survey extents

Figure 1





Gradiometer Survey Extents

0

50

m

N

**Processing History**  
Group Zero Median Traverse:  $\pm 5\text{nT}$  thresholds applied to all grids  
Zero Median Traverse:  $\pm 1\text{nT}$  thresholds applied to all grids  
Zero Mean Traverse:  $\pm 5\text{nT}$  thresholds applied to selected ferrous dominated grids  
Deslope: applied to selected grids to remove grid edge discontinuities  
Destagger: -2 shift applied to all grids with further shifts of  $\pm 1$  applied to selected grids and traverses

Contains OS data © Crown copyright [and database right] (2024)  
This material is for client report only © Lefort Geophysics. No unauthorised reproduction.

|        |              |              |     |
|--------|--------------|--------------|-----|
| Date:  | 04/10/2025   | Revision:    | 0   |
| Scale: | 1:1500 at A3 | Illustrator: | RDL |





Gradiometer Survey Extents

0

50

m

N


**Processing History**  
Group Zero Median Traverse:  $\pm 5\text{nT}$  thresholds applied to all grids  
Zero Median Traverse:  $\pm 1\text{nT}$  thresholds applied to all grids  
Zero Mean Traverse:  $\pm 5\text{nT}$  thresholds applied to selected ferrous dominated grids  
Deslope: applied to selected grids to remove grid edge discontinuities  
Destagger: -2 shift applied to all grids with further shifts of  $\pm 1$  applied to selected grids and traverses

Contains OS data © Crown copyright [and database right] (2024)  
This material is for client report only © Lefort Geophysics. No unauthorised reproduction.

|        |              |              |     |
|--------|--------------|--------------|-----|
| Date:  | 04/10/2025   | Revision:    | 0   |
| Scale: | 1:1500 at A3 | Illustrator: | RDL |

XY trace plot

Figure 3





050m

050m

N

Processing History

Group Zero Median Traverse: ±5nT thresholds applied to all grids

Zero Median Traverse: ±1nT thresholds applied to all grids

Zero Mean Traverse: ±5nT thresholds applied to selected ferrous dominated grids

Deslope: applied to selected grids to remove grid edge discontinuities

Destagger: -2 shift applied to all grids with further shifts of +/-1 applied to selected grids and traverses

Contains OS data © Crown copyright [and database right] (2024)

This material is for client report only © Lefort Geophysics. No unauthorised reproduction.

|        |              |              |     |
|--------|--------------|--------------|-----|
| Date:  | 04/10/2025   | Revision:    | 0   |
| Scale: | 1:1500 at A3 | Illustrator: | RDL |



Greyscale plot (unprocessed raw data)

Figure 5

