

Specifications Table for EPRA14-18DW7

Dimensions	Unit		Height	mm	1003
			Width	mm	1270
			Depth	mm	533
Weight	Unit			kg	150
Operation range	Cooling	Min.		°CDB	10
		Max.		°CDB	43
	Domestic hot water	Min.		°CDB	-28
		Max.		°CDB	35
Sound power level	Heating	Nom.		dBA	56.0
	Cooling	Nom.		dBA	65.0
Sound pressure level	Heating	Nom.		dBA	43.0
		Cooling		Nom.	dBA
Refrigerant	Type				R-32
	GWP				675.0
	Charge			tCO2Eq	2.84
	Charge			kg	4.2
Piping connections	Level difference	IU - OU	Max.	m	10.0
Power supply	Name				W1
	Phase				3~
	Frequency			Hz	50
	Voltage			V	400
Current	Recommended fuses			A	16
Notes				(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)	
				(2) - Condition 2: cooling Ta 35°C - LWE 7°C	

	(DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C)
	(3) - The sound pressure level is measured via a microphone at a certain distance from the unit. It is a relative value depending on the distance and acoustic environment. Refer to sound spectrum drawing for more information. Condition: Ta DB/WB 7°C/6°C - LWC 3
	(4) - The sound pressure level is measured via a microphone at a certain distance from the unit. It is a relative value depending on the distance and acoustic environment. Refer to sound spectrum drawing for more information. Condition: Ta 35°C - LWE 7°C (DT =
	(5) - Percentage of heating capacity at Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)