



Kingsmere Surfacing Limited

Document Kingsmere
3rd March 2026

Station Yard
Lower Station Road
Gillingham
Dorset SP8 4PZ

Tel: 01747 822080
Mobile: 07711 279549

Email: info@kingsmeresurfacing.co.uk
Website: www.kingsmeresurfacing.co.uk

QUOTATION

Mr Grey
Moor Hill
Fovant
Salisbury
SP3 5LB

27th August 2024

To supply labour, plant and materials to carry out the following surfacing works at the above address,

DRIVEWAY/PARKING AREA IN DECORATIVE RESIN BOUND AGGREGATE.

Declined

- All preparations carried out by customer.
- For resin surface and concrete we need a working depth of 120mm.
- Customer using type 3 aggregate for the subbase compacted in layers to a depth of 130mm.
- Lay a no fines permeable concrete compacted to a depth of 100mm.
- Lay a bead edge where required to retain the resin bound aggregate.
- Lay a decorative resin bound aggregate trowelled to a depth of 20mm.
- Leave clean and tidy.

For a total sum of [REDACTED] + Vat per²m

DRIVEWAY/PARKING AREA IN A TARMAC WITH A BASE AND TOPCOAT.

This offer was accepted.

- All preparations carried out by customer.
- Tarmac surface we need a working depth of 75mm.
- Customer using type 3 aggregate for the subbase compacted in layers to a depth of 150mm.
- lay a 20mm open graded base coat compacted to a depth of 50mm.
- lay a 10mm drain wright wearing surface tarmac compacted to a depth of 30mm.
- leave clean and tidy.

For the total sum of [REDACTED] + Vat per²m

DRIVEWAY/PARKING AREA IN A PERMEABLE BLOCK PAVING.

Declined

- All preparations carried out by customer.
- Block paving needs to be prepped to a depth of 100mm.
- Customer using type 3 aggregate for the subbase compacted in layers to a depth of 130mm.
- Lay a washed limestone sand to a depth of 50mm.
- Lay a std block paving in a liner or herringbone pattern.