

L30 STAIRS/WALKWAYS/BALUSTRADES BALUSTRADE(S) AND HANDRAILS(S)

Detailed description

Juliet balcony balustrade system capable of using varying glass thicknesses from 12mm to 21.52mm toughened and laminated glass.

Side fix channel retention system suitable for façade mounting, frame mounting and reveal fixing. We also recommend that you visit our website for CAD drawings, BIM Objects, safety certificates, portfolio, news and essential contact details. It is also recommended that you seek guidance from Q-railing Architectural team to ensure that your specifications are fit for purpose and comply with varying loading requirements.

System includes:

- Aluminium profiles and rubber sets for fixing of glass
- Design criteria 0.74kN/m.

Product Guidance:

Even top quality materials are only as good as the workmanship used to process them. Easy installation techniques are created by modular parts with maximum precision fittings. Safety is very important in railing manufacture, vertical and horizontal loadings must be adsorbed. Reference should be made between product test certification and loading requirements set out in the current building regulations and British standards to ensure that the overall system has full compliance.

Product Guidance:

Our website address: www.q-railing.com

Company: Q-railing
Telephone: 0800 781 4245
Fax: 0800 781 4246
Email: ukconsultant@q-railing.com
Address: Q-railing UK
Unit 1. Tunstall Arrow
James Brindley way
Stoke-on-Trent
Staffs
ST6 5GF

Product reference: Q-railing, Easy Glass® View full glass railing system, suitable for façade mounting, frame mounting and reveal fixing.

Profile sets:

- 86.6923.100.08 (Complete set including 2 profiles for 1100mm tall glass, 2 top end caps, 4 cover caps, 2 bottom end caps) Matt silver effect also available in PPC any RAL colour can be achieved. Architect to confirm RAL number
- 16.6923.500.00 Profile, 5000mm long to be cut to size tbc (Raw finish – available for PPC)
- 16.6923.500.08 Profile, 5000mm long to be cut to size tbc (Matt silver effect finish)

Glazing infill:

Type: As drawing _____ Suitable glazing thickness: 12mm to 21.52mm

Rubber seals:

- 19.6923.114.00 for 13.52mm toughened laminated glass
- 19.6923.118.00 for 17.52mm toughened laminated glass
- 19.6923.122.00 for 21.52mm toughened laminated glass

Note refer to Q-railing test data for glass specification in relation to specific loading criteria required for various building types. Email ukconsultant@q-railing.com

For UK specification queries please use the above contact information to liaise directly with Q-railings specification team to