



# Manual centre-pivot for low pitch roofs

Made for homes with low pitches (10°-20°). GBL

Perfect for bringing daylight and fresh air into single-storey extensions, the Low pitch roof window is the best solution for roofs with a pitch between 10°-20°. The product is designed to be fully watertight at a low pitch and features glass-to-edge technology, ensuring a seamless and aesthetic installation.

- Tested in one of northern Europe's largest wind tunnels for wind and water resistance.
- Fast and simple installation.
- Available with EDG flashing for profiled tiles ranging from 15mm to 120mm, approved for roof pitches between 10° and 20°.
- Available with EDQ flashing for click metal roofs with standing seams ranging between 25mm to 35mm, approved for roof pitches between 10° and 20°.

Find EPDs at [velux.co.uk/technical-library](http://velux.co.uk/technical-library)

Roof pitch



## Interior finish options



**White painted**  
High quality natural pine treated with a water-based white paint for a discreet wood grain look

## Glazing options

|  |                        |
|--|------------------------|
|  | Triple glazing<br>--15 |
|  | ✓                      |
|  | ✓                      |
|  | ✓                      |
|  | ✓                      |
|  |                        |
|  |                        |

Thermal transmittance of glazing (U<sub>g</sub> value)

0.7

Read more about glazing specifications on page 162.

## Blinds and shutters

- Consider interior blinds for light control, and exterior Anti-Heat blinds or shutters for added heat protection.

Read more on page 89.

## Upgrade to a solar roof window

- Upgrade to a solar roof window with the conversion kit (KSX). Includes a rain sensor that closes the roof window when it rains.
- Compatible with all sizes except SK01.

Read more on page 148.



|                                 |                    |       |       |        |        |       |                |
|---------------------------------|--------------------|-------|-------|--------|--------|-------|----------------|
| External frame sizes (w x h) cm | W/m <sup>2</sup> K | CK04  | MK04  | MK06   | PK04   | SK01  | SK06           |
|                                 |                    | 55x98 | 78x98 | 78x118 | 78x140 | 94x98 | 114x70 114x118 |

|                          |                          |                          |                          |                          |                          |                          |                          |
|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|

## White painted

|  |              |                                       |     |     |     |     |     |     |      |
|--|--------------|---------------------------------------|-----|-----|-----|-----|-----|-----|------|
|  | GBL S10G03*  | For profiled tiles up to 120mm        | 1.3 | 646 | 708 | 766 | 861 | 908 | 1015 |
|  | GBL S10G06** | For click metal roofs between 25-35mm | 1.3 | 623 | 682 | 758 | 832 | 771 | 982  |

## Recommended blinds and shutters

|                         |                                  |    |    |    |     |     |     |
|-------------------------|----------------------------------|----|----|----|-----|-----|-----|
| DKL Standard Collection | Manual Blackout blind (interior) | 78 | 90 | 96 | 102 | 110 | 120 |
|-------------------------|----------------------------------|----|----|----|-----|-----|-----|

\* Package includes roof window, flashing, Insulation BDx and Underfelt collar BFX suitable for installation into profiled tiles up to 120mm.

\*\* Package includes window, EDQ flashing, underfelt collar and insulation collar BDx suitable for installation into click metal roofs between 25-35mm.

All prices in GBP (£)

Find all sizes and prices at [velux.co.uk](http://velux.co.uk)