

FOUL PHASE: 1									
MH No.	DIAGRAM	MANHOLE DIMENSION (mm)	MANHOLE TYPE	COVER TYPE	COVER LEVEL (m)	INVERT LEVEL (m)	DEPTH TO SOFFIT (m)	EASTING (m)	NORTHING (m)
F1		1200ø	Type B	D400	44.821	42.803	1.867	392667.634	164296.210
F2		1200ø	Type B	D400	44.537	42.530	1.857	392654.772	164285.352
F3		1200ø	Type B	D400	43.840	41.750	1.940	392625.365	164257.871
F4		1350ø	Type C	D400	44.173	42.831	1.192	392701.684	164257.801
F5		1200ø	Type B	D400	44.635	42.480	2.005	392683.672	164241.370
F6		1200ø	Type B	D400	44.359	41.396	2.813	392660.806	164219.345
F7		1200ø	Type B	D400	43.890	41.501	2.239	392745.917	164218.463
F8		1200ø	Type B	D400	43.675	41.265	2.260	392730.205	164208.012
F9		1200ø	Type B	D400	43.952	41.030	2.772	392698.202	164178.241
F10		1200ø	Type B	D400	43.497	40.843	2.505	392715.675	164157.836
F11		1200ø	Type B	D400	42.671	40.730	1.791	392744.274	164117.180
F12		1200ø	Type B	D400	43.001	40.100	2.751	392732.879	164133.594
F13		1200ø	Type A	D400	43.229	39.858	3.221	392703.226	164112.778
F14		1200ø	Type B	D400	42.713	40.240	2.323	392642.248	164118.604
F15		1200ø	Type B	D400	42.872	40.000	2.722	392647.921	164106.315
F16		1200ø	Type A	D400	43.058	39.300	3.608	392665.974	164083.274
F17		1200ø	Type A	D400	42.715	39.220	3.345	392653.760	164074.579
F18		1200ø	Type B	D400	41.510	39.500	1.860	392603.796	164097.959
F19		1200ø	Type A	D400	41.822	38.670	3.002	392618.508	164060.959
F20		1350ø	Type C	D400	42.082	40.561	1.370	392547.599	164085.587
F21		1200ø	Type B	D400	41.352	39.050	2.152	392565.870	164040.017
F22		1200ø	Type A	D400	41.385	38.135	3.025	392601.080	164053.993
F23		1200ø	Type A	D400	41.896	38.430	3.316	392633.141	164001.579
F24		1200ø	Type A	D400	42.169	37.489	4.455	392621.429	164000.210
F25		1200ø	Type A	D400	41.731	37.334	4.172	392600.262	163992.343
F26		1200ø	Type A	D400	41.508	37.256	4.027	392590.753	163985.542
F27		1200ø	Type A	D400	40.849	37.025	3.599	392558.656	163972.443
F28		1200ø	Type B	D400	39.684	36.790	2.669	392525.959	163959.488
F29		1200ø	Type B	D400	41.612	39.762	1.700	392936.695	163960.847
F30		1200ø	Type B	D400	41.356	39.455	1.751	392916.331	163947.056
F31		1200ø	Type B	D400	40.133	38.383	1.600	392933.786	163893.720
F32		1200ø	Type B	D400	40.862	38.084	2.629	392919.132	163912.684
F33		1200ø	Type A	D400	41.032	37.790	3.092	392902.000	163928.415
F34		1200ø	Type A	D400	41.143	37.574	3.419	392876.582	163941.719
F35		1200ø	Type A	D400	41.246	37.417	3.679	392861.711	163950.086
F36		1200ø	Type A	D400	41.366	37.299	3.918	392846.053	163971.689
F37		1200ø	Type B	D400	43.289	41.415	1.724	392799.735	164114.798

FOUL PHASE: 1									
MH No.	DIAGRAM	MANHOLE DIMENSION (mm)	MANHOLE TYPE	COVER TYPE	COVER LEVEL (m)	INVERT LEVEL (m)	DEPTH TO SOFFIT (m)	EASTING (m)	NORTHING (m)
F75		1200ø	Type B	D400	43.758	40.750	2.858	392314.285	164306.593
F76		1200ø	Type B	D400	43.806	40.672	2.984	392313.134	164294.969
F77		1200ø	Type A	D400	44.212	40.446	3.616	392313.079	164260.975
F78		1200ø	Type A	D400	44.468	40.340	3.978	392313.134	164245.129
F79		1200ø	Type A	D400	44.626	40.264	4.212	392317.082	164234.492
F80		1200ø	Type A	D400	44.966	40.087	4.729	392328.377	164210.422
F81		1200ø	Type A	D400	45.055	40.037	4.868	392332.020	164203.796
F82		1350ø	Type C	D400	45.271	44.015	1.106	392353.752	164201.763
F83		1200ø	Type A	D400	45.299	39.898	5.250	392349.713	164193.545
F84		1200ø	Type A	D400	45.304	39.750	5.404	392357.942	164188.458
F85		1200ø	Type A	D400	45.233	39.530	5.553	392362.265	164182.432
F86		1200ø	Type A	D400	45.014	39.457	5.407	392365.738	164172.048
F87		1200ø	Type A	D400	44.000	39.184	4.666	392378.241	164133.059
F88		1350ø	Type C	D400	44.698	43.351	1.198	392309.783	164170.172
F89		1350ø	Type C	D400	44.501	43.067	1.283	392321.194	164164.101
F90		1350ø	Type C	D400	44.164	42.814	1.200	392312.024	164145.600
F91		1200ø	Type A	D400	43.811	40.334	3.327	392324.264	164105.753
F92		1350ø	Type C	D400	42.399	41.024	1.225	392341.252	164053.356
F93		1200ø	Type B	D400	43.189	40.634	2.405	392331.229	164082.919
F94		1200ø	Type A	D400	43.534	39.620	3.764	392327.202	164095.668
F95		1200ø	Type A	D400	43.498	38.955	4.318	392384.437	164114.158
F96		1200ø	Type A	D400	42.984	38.815	3.944	392390.408	164094.056
F97		1200ø	Type A	D400	42.470	38.683	3.562	392397.054	164075.355
F98		1200ø	Type B	D400	41.745	39.500	2.095	392415.931	164081.378
F99		1200ø	Type A	D400	42.233	38.624	3.384	392401.915	164068.042
F100		1200ø	Type A	D400	41.966	38.549	3.192	392410.811	164061.157
F101		1200ø	Type B	D400	41.453	38.343	2.884	392435.721	164042.905
F102		1200ø	Type B	D400	41.250	38.250	2.775	392444.412	164031.826
F103		1200ø	Type B	D400	41.355	39.317	1.888	392495.753	164063.272
F104		1200ø	Type B	D400	41.800	38.877	2.772	392510.279	164031.234
F105		1200ø	Type B	D400	41.753	38.722	2.880	392514.856	164019.693
F106		1200ø	Type B	D400	41.172	38.513	2.508	392485.753	164007.954
F107		1200ø	Type B	D400	40.714	37.539	2.950	392458.145	163997.062
F108		1200ø	Type B	D400	40.073	37.240	2.608	392473.935	163955.729
F109		1200ø	Type A	D400	39.761	34.253	5.283	392474.200	163932.443
F110		1200ø	Type A	D400	39.671	34.198	5.248	392465.907	163932.443

FOUL PHASE: 1									
MH No.	DIAGRAM	MANHOLE DIMENSION (mm)	MANHOLE TYPE	COVER TYPE	COVER LEVEL (m)	INVERT LEVEL (m)	DEPTH TO SOFFIT (m)	EASTING (m)	NORTHING (m)
F38		1200ø	Type B	D400	43.712	41.054	2.507	392823.373	164131.392
F39		1200ø	Type A	D400	43.642	40.411	3.081	392853.648	164089.738
F40		1200ø	Type A	D400	43.466	40.300	3.016	392856.561	164081.407
F41		1200ø	Type B	D400	43.232	40.190	2.892	392851.955	164071.044
F42		1200ø	Type A	D400	41.759	36.955	4.654	392815.312	164013.139
F43		1200ø	Type A	D400	41.644	36.558	4.936	392766.231	163979.430
F44		1200ø	Type A	D400	38.767	35.507	3.110	392622.984	163913.666
F45		1200ø	Type A	D400	38.549	35.132	3.267	392566.816	163911.434
F46		1200ø	Type A	D400	39.621	34.808	4.588	392531.319	163923.231
F47		1200ø	Type A	D400	38.130	34.548	3.357	392494.630	163910.148
F48		1200ø	Type A	D400	39.733	34.406	5.102	392473.383	163909.460
F53		1200ø	Type B	D400	45.887	43.196	2.542	392537.457	164312.030
F54		1200ø	Type B	D400	46.118	44.268	1.700	392645.913	164351.296
F55		1200ø	Type B	D400	45.328	43.380	1.798	392606.416	164321.638
F56		1200ø	Type B	D400	45.090	42.840	2.100	392567.934	164290.052
F57		1200ø	Type A	D400	45.267	42.050	3.067	392556.246	164286.299
F58		1200ø	Type B	D400	44.691	41.929	2.612	392550.901	164269.216
F59		1200ø	Type B	D400	45.945	43.830	1.965	392521.891	164293.751
F60		1200ø	Type B	D400	44.859	41.970	2.739	392541.697	164267.167
F61		1200ø	Type B	D400	44.460	41.450	2.860	392547.146	164260.174
F62		1200ø	Type A	D400	44.673	41.146	3.376	392511.870	164231.356
F63		1200ø	Type A	D400	45.954	42.200	3.604	392439.561	164261.938
F64		1200ø	Type A	D400	44.837	40.794	3.893	392463.226	164208.930
F65		1200ø	Type A	D400	44.394	40.545	3.700	392429.830	164193.718
F66		1200ø	Type A	D400	44.429	40.361	3.918	392403.776	164184.944
F67		1200ø	Type B	D400	46.201	44.321	1.730	392443.001	164293.047
F68		1200ø	Type B	D400	45.482	43.370	1.962	392425.806	164330.748
F69		1200ø	Type B	D400	45.553	43.585	1.817	392451.103	164373.322
F70		1200ø	Type B	D400	45.055	42.701	2.204	392414.533	164356.822
F71		1200ø	Type B	D400	45.436	43.097	2.188	392387.031	164273.516
F72		1200ø	Type B	D400	44.764	42.650	1.964	392371.684	164306.101
F73		1200ø	Type B	D400	44.300	41.700	2.450	392359.992	164331.777
F74		1200ø	Type B	D400	43.782	40.808	2.824	392319.878	164313.282